Our RB Booster family just got bigger

ONE FAMILY, ONE PROMISE: INSTANT STARTING POWER

	RB 1500 Everyday cover	RB 2000 Everyday cover, more starts	RB 3000 Everything on the driveway	RB 4000 For when starting is the job
				
Vehicles	Smaller petrol & diesel cars	Hatchbacks, saloons, estates & compact SUVs - petrol & smaller diesels	Cars, SUVs, pickups, vans, campers and boats	All 12V vehicles, plus heavier goods vans and tractors
Starts per charge	Up to 20	Up to 25	Up to 30	Up to 45
For engine size (up to)	Petrol: 6L Diesel: 3L	Petrol: 6L Diesel: 3L	Petrol: 8L Diesel: 6L	Petrol: 10L Diesel: 8L
Best suited to	Second cars, city driving and small vehicles that sit	One-car households – the everyday drive	Multi-vehicle households and the self-employed	Workshops, fleets, farms and recovery

© CTEK SWEDEN AB

CTEK

RB Boosters

INSTANT STARTING POWER. CTEK BOOSTERS GET YOU BACK ON THE MOVE, FAST

2 YEAR WARRANTY

COMPACT & PORTABLE

- Fits a glove box or bag
- Easy to store and carry
- Detachable cables for convenience and longer life

PROFESSIONAL VERSATILITY

- Trusted by workshops and professionals
- Power and functionality for added everyday value
- Powerful performance in a portable solution



POWER BANK

FLASH LIGHT

POWER WHEN IT MATTERS

- 1500A - 4000A of starting power
- Reliable starts in cold conditions and low batteries
- More starts, more confidence

ENGINEERED FOR RELIABILITY

- Multi-cell internal battery design
- Spark-proof and reverse-polarity protected
- Swedish quality you can trust

© CTEK SWEDEN AB

CTEK

Technical data

	RB 1500	RB 2000
Number of starts	20	25
For engine size (up to)	Petrol: 6L, Diesel: 3L	Petrol: 6L, Diesel: 3L
Battery peak current	1500A	2000A
Start Current	450A (1 sec), 230 A (5 sec)	650A (1 sec), 300A (5 sec)
Peak Current (Measured for 0.1sec)	1300A (0.1 sec), 1500 A (0.01 sec)	1500A (0.1 sec), 1800 A (0.01 sec)
Fast charging time	1 hour 30 mins	1hour 50 mins
Internal Battery pack type	4S1P	4S1P
Internal Battery Cell Chemistry	Lithium Manganese Nickel And Cobalt	Lithium Manganese Nickel And Cobalt
Start voltage	12V	12V
Dimensions (L X W X H)	198 x 93 x 36 mm	198 x 93 x 36 mm
Net weight (unit with cables)	742 g	783 g
Degree of protection	IP54	IP54
Detachable Charging Cable Length Output	0.25 meter	0.25 meter
Warranty	2 years	2 years

© CTEK SWEDEN AB